

1<sup>ST</sup> CHOICE **EQUIPMENT EXPERTS**

A large, abstract graphic on the left side of the page features a stylized human figure in profile, facing right. The figure is composed of thick, rounded shapes in a reddish-orange color. It has a dark blue head and neck area, and a dark blue arm that extends downwards and to the left. The background behind the figure is a dark teal color.

JET HEAT  
HEATING  
AIR CONDITIONING  
DEHUMIDIFICATION  
SOLAR HYBRID LIGHT TOWERS



1ST CHOICE EQUIPMENT EXPERTS

# REIC SPECIALTY

## WHO WE ARE

### Private Equity – Backed By Kinderhook Industries

- An Experienced Investment Company With a Strong Track Record of Success
- Over \$5 Billion of Committed Capital

### WHAT WE'RE MADE OF

- 6 Specialty Rental Brands Serving North America
- 20 Branches – 13 States and 3 Provinces
- Worldwide Intellectual Property Ownership for Jet Heat Flameless Heaters
- North American Distribution For Verdegro Solar Hybrid Light Towers
- One of the Youngest and Largest Climate Control Fleets in North America
- Over 200 Employees and growing
- Executive Team Over 150 Years Specialty Rental Equipment Experience

### LOCATIONS

#### UNITED STATES

South Windsor, Connecticut  
South Plainfield, New Jersey  
Wilmington, Delaware  
Chesapeake, Virginia  
Fairmont, West Virginia  
Marysville, Ohio  
Livonia, Michigan

St. Charles, Illinois  
Chaska, Minnesota  
Williston, North Dakota  
Denver, Colorado  
Brighton, Colorado  
Edmond, Oklahoma  
Lakewood, Washington  
Midland-Odessa, Texas

#### CANADA

Brantford, Ontario  
Red Deer, Alberta  
Fort McMurray, Alberta  
Fort St. John, British Columbia  
Anzac, Alberta  
Sudbury, Ontario  
Kitimat, British Columbia





1ST CHOICE EQUIPMENT EXPERTS



[REICSpecialty.com](http://REICSpecialty.com)

 CAHILL  
SERVICES

 TCR  
Total Construction Rentals

 CHI  
COMPANIES

INDUSTRIAL  
DRYING  
SOLUTIONS  
 IDS

 MIDSTREAM  
EQUIPMENT



1ST CHOICE EQUIPMENT EXPERTS

# RENTAL AIR CONDITIONING

**12  
TON  
AC**



**25  
TON  
AC**



**30  
TON  
AC**



**45  
TON  
AC**



**80  
TON  
AC**



## SPECIFICATIONS

<b>Cooling Capacity</b>	135,000 BTU
<b>Refrigerant</b>	R-410A
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	63
<b>Weight</b>	2,200
<b>L x W x H</b>	95.5" x 35" x 75.7"

<b>Cooling Capacity</b>	25 Tons
<b>Refrigerant</b>	R-410A
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	48 Cooling / 123 Heating
<b>Weight</b>	3,200
<b>L x W x H</b>	92" x 128" x 63"

<b>Static Pressure / CFM</b>	6.5" static @4,500CFM
<b>Refrigerant</b>	R-410A
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	114
<b>Weight</b>	5,000
<b>L x W x H</b>	97" x 72" x 98.25"

<b>Static Pressure / CFM</b>	6.5" static @6,000CFM
<b>Refrigerant</b>	R-410A
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	125
<b>Weight</b>	7,200
<b>L x W x H</b>	88" x 96" x 99.75"

<b>Cooling Capacity</b>	960,000BTU
<b>Refrigerant</b>	R-410A
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	218
<b>Weight</b>	5,700
<b>L x W x H</b>	12' x 8' x 8'2"

Feature Units. Full product offering available upon request.



1ST CHOICE EQUIPMENT EXPERTS

# RENTAL AIR CONDITIONING

## PORTABLE COOLING

1 TON  
TO  
5 TON  
AC



MODEL	COOLING/BTU	CFM	POWER	WEIGHT WxDxH	REFRIGERANT
1 Ton	13,200	405	115V 60H 12 Amps	185 lbs 20.6x26.4x41"	R410A
1.5 Ton	16,800	470	115V 60H 20 Amps	181 lbs 20.6x26x41"	R410A
2 Ton	21,000	560	208V 60H 15 Amps	196 lbs 20.6x26.4x41"	R410A
3 Ton	37,000	882	208V 60H 30 Amps	254 lbs 26.0x33.3x52.4"	R410A
5 Ton	60,000	2,000	208V 60H 50 Amps	661 lbs 28.9x 1.5x59.8"	R410A

## PORTABLE COOLING WITH HEAT PUMP

1 TON &  
1.5 TON



MODEL	COOLING/BTU	CFM	POWER	WEIGHT WxDxH	REFRIGERANT
1 Ton w/ Heat Pump	13,200	305	115V 60H 20 Amps	230 lbs 20.6x26.4x41"	R410A
1.5 Ton w/ Heat Pump	16,800	400	115V 60H 20 Amps	190 lbs 20.6x26.4x41"	R410A

## LGR DEHUMIDIFIERS

280  
TO  
400  
CFM



MODEL	CFM	WATER REMOVAL	DIMENSIONS WxDxH	WEIGHT	POWER
7000 XLi	280	130 PTS/Day	20x33.5x20"	106 lbs	115V 8.8Amps
3500 i	400	170 PTS/Day	24x 40.5x23	157 lbs	120V 10.8Amps

PHOENIX  
250  
MAX



MODEL	CFM	WATER REMOVAL	DIMENSIONS WxDxH	WEIGHT	POWER
250 Max	365	145 PTS/Day	20x23x40"	119 lbs	120V 8.2Amps

Feature Units. Full product offering available upon request.



1ST CHOICE EQUIPMENT EXPERTS



### Portable LGR

- 120V "plug and play"
- Control moisture quickly and easily
- Built-in pumping system with attached drainage hose
- Easy to operate and maneuver
- Handle and wheels for ease of movement

### Applications:

For use in areas with high humidity, especially in construction sites and in facilities following fire or water damage



## PORTABLE COOLING & DEHUMIDIFICATION

### FEATURES

- Multiple power Voltages available (110V-480V)
- Easy to setup, operate and maneuver
- Portable and mobile units with easy to roll casters attached
- 110V operation on many units - simply plug into outlet and cooling begins
- Air cooled or water-cooled options in fleet
- Heat pump options available (heating and cooling in one unit)
- Portable heating and cooling available with 120V unit
- Contact for 24/7 emergency delivery available
- Delivery, installation and removal available

### PORTABLE AIR CONDITIONING FOR MANY APPLICATIONS:

Office and commercial spaces for short term cooling, Temporary cooling in computer rooms and for server racks, assisted living, hospitals and medical facilities, commercial and retail spaces, manufacturing areas, educational settings (classrooms and lecture halls)





1ST CHOICE EQUIPMENT EXPERTS

# RENTAL DESICCANT DEHUMIDIFIERS

Feature Units. Full product offering available upon request.

**2,250  
CFM DH**



**4,500  
CFM DH**



**5,000  
CFM DH**



**7,500  
CFM DH**



**15,000  
CFM DH**



## SPECIFICATIONS

<b>CFM (Process)</b>	2,250
<b>Static Pressure</b>	2"
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	52
<b>Weight</b>	1,250
<b>L x W x H</b>	89" x 29" x 58"

<b>CFM (Process)</b>	4,500
<b>Static Pressure</b>	4"
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	108
<b>Weight</b>	1,950
<b>L x W x H</b>	98" x 46" x 77"

<b>CFM (Process)</b>	5,000
<b>Static Pressure</b>	5"
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	148
<b>Weight</b>	4,400
<b>L x W x H</b>	101" x 50" x 96"

<b>CFM (Process)</b>	7,500
<b>Static Pressure</b>	5"
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	178
<b>Weight</b>	4,400
<b>L x W x H</b>	101" x 50" x 96"

<b>CFM (Process)</b>	15,000
<b>Static Pressure</b>	6"
<b>Voltage / Phase / Hertz</b>	480/3/60
<b>Full Load Amps</b>	345
<b>Weight</b>	9,500
<b>L x W x H</b>	140" x 100" x 101"

Some dual-fuel units available that operate on gas and/or electric.



# HEATERS

Feature Units. Full product offering available upon request.

## DIRECT FIRED HEATERS

150K  
TO  
1.4M  
BTUs



BTU	POWER	WEIGHT	DIMENSION LxWxH	FUEL TYPE	CERTIFICATION
150,000	120V 7 Amp	100 lbs	31"x22"x23"	Propane/NG	AGA/CSA/ETL
250,000	120V 14 Amp	150 lbs	40"x27"x29"	Propane/NG	AGA/CSA/ETL
400,000	120V 9 Amp	220 lbs	45"x28"x35"	Propane/NG	AGA/CSA/ETL
500,000	120V 7 Amp	135 lbs	42"x24"x27"	Propane/NG	AGA/CSA/ETL
700,000	120V 11 Amp	280 lbs	51"x32"x41"	Propane/NG	AGA/CSA/ETL
1,000,000	120V 12 Amp	195 lbs	48"x25"x31"	Propane/NG	AGA/CSA/ETL
1,400,000	120V 13 Amp	330 lbs	54"x32"x41"	Propane/NG	AGA/CSA/ETL

350K  
TO  
1.0M  
BTUs



## INDIRECT FIRED HEATERS

BTU	PERFORMANCE	WEIGHT	DIMENSION LxWxH	FUEL TYPE	CERTIFICATION
350,000	2500CFM	580 lbs	83"x37"x52"	Propane/NG/ Diesel	AGA/CSA/ETL
500,000	3100CFM	580 lbs	83"x37"x52"	Propane/NG/ Diesel	AGA/CSA/ETL
750,000	4280CFM	865lbs	94"x32"x53"	Propane/NG	USA/CAN
1,000,000	4075CFM	1300 lbs	120"x31"x54"	Propane/NG/ Diesel	AGA/CSA/ETL

10 TO  
60  
KWs



## ELECTRIC HEATERS

KW	VOLTS	AMPS	PHASE
10	240	42	1
15	240	36	3
15	480	18	3
15	208	42	3
15	240	62.5	1
60	480	68	3
150	480	196	3





1ST CHOICE EQUIPMENT EXPERTS

# MAKE-UP AIR HEATERS

Feature Units. Full product offering available upon request.

**650K  
BTU**



**1.6M  
BTU**



**2.5M  
BTU**



**4.5M  
BTU**



## SPECIFICATIONS

Up to 650,000 BTU, modulating  
5,500 cfm output of heat  
4" of static pressure  
LP or NG  
120v at 12.7 amps  
20" duct outlet

Units are **STACKABLE**  
Ducting up to 100'  
Dimensions:  
L68" x W30" x H43.5"  
Weight: 500 lbs

Up to 1,600,000 BTU,  
modulating  
9,400 cfm output of heat  
1ph or 3ph 230V at 40A  
LP or NG  
Designed for metal ducting

Units are **STACKABLE**  
Forklift pockets  
Dimensions:  
L92" x W31.5" x H62.5"  
Weight: 995 lbs

Up to 2,500,000 BTU,  
modulating  
14,737 cfm heated output  
1ph or 3ph 230V at 60A  
LP or NG  
Designed for metal ducting

Units are **STACKABLE**  
Forklift pockets  
Dimensions:  
L111" x W31.5" x H78.5"  
Weight: 1640 lbs

Up to 4,500,000 BTU,  
modulating  
24,390 CFM heated output  
230v 3PH 56A OR  
480v 3PH 28A  
LP or NG

Designed for metal ducting  
Units are stackable  
Forklift pockets  
Dimensions:  
L126" x W44" x H79"  
Weight: 2,327 lbs



## 1ST CHOICE EQUIPMENT EXPERTS

The CH15HS Jet Heater uses a patented turbofan jet engine technology to achieve industry leading heating efficiency. With greater than 95% efficiency and less than 60% CO<sub>2</sub> emissions, the CH15HS is the most fuel friendly and the cleanest flameless heater in its class.

# JET HEATER

## CH15HS



## FEATURES

- 1.4 Million BTU Equivalent
- 2.9-4.9 GPH Fuel Consumption
- Hot air delivery up to 500 Ft
- 200° F temperature rise
- 3900-7200 CFM
- 20" above WC static pressure
- 110% secondary containment
- Clean breathable air
- Self-contained unit (No external power required)
- Variable setting — Low, Medium, High
- Onboard diagnostics with safety shutdown
- Rugged design for durability

## ENVIRONMENTAL IMPACT

### Emissions Reduction

- 97% engine efficiency
- Average reduction of 127 tons of CO<sub>2</sub> — Equivalent CO<sub>2</sub> of 140,000 pounds of coal burned

### Fuel Consumption

- As low as 2.9 GPH fuel consumption
- Reduce Fuel costs up to 50%
- Most fuel efficient diesel flameless heater

## TOTAL PROJECT SAVINGS

- Up to \$140,000 annually per heater
- Replace up to 8 indirect heaters with 1 Jet Heater



**HEAT DELIVERED  
UP TO 500' AWAY**

View the Demo and see it in action

### APPLICATIONS

#### OIL & GAS

Drill Deck, Pump Station & Water Line Heating  
Frost Prevention System  
Multiple Wellheads & BOPs Heating  
Pipeline Heating & Thermal Conditioning

#### CONSTRUCTION

Concrete Curing | Ground Thaw  
Aggregate Heating | Shotcreting  
Multi-Storey Construction Heating  
Worker Comfort

#### COATING & PAINTING

Tank Coating & Curing  
Moisture & Humidity Control  
|Dehumidification | Surface Preparation  
Auxiliary Heat | De-Icing



1ST CHOICE EQUIPMENT EXPERTS

The Cahill Hybrid LT is a solar powered light tower combined with a Kubota Diesel powered DC Generator. With an extremely low fuel consumption, the Cahill Light Tower will run up to 35 days before refueling.



## ENVIRONMENTAL IMPACT

### Emissions Reduction

- Solar Hybrid Battery Powered
- Average reduction of 56 tons of CO<sub>2</sub>
- Equivalent CO<sub>2</sub> of 62,000 pounds of coal burned



### Fuel Data

- As low as 0.2 GPH fuel consumption
- Reduce fuel costs up to 50%
- Auto on/off Dawn to Dusk



# SOLAR HYBRID LIGHT TOWER

## FEATURES

- Hybrid technology - Solar and DC Generator
- Average 3 hours of engine runtime/day
- Up to 8 hours runtime on solar and battery between charges
- Dawn to Dusk feature - automatically shuts off during daylight hours
- Remote monitoring, start and stop technology
- 68,000 Lumens of LED light
- Positive air shutoff
- Winter operating package
- Operating costs savings up to \$80/day

## TOTAL PROJECT SAVINGS

- Up To \$25,000 Annually/Light Tower

## SMALL STEPS LEAD TO BIG CHANGE!

Reduce Engine Emissions By Up To 90%

#NETZERO



[REICSpecialty.com](http://REICSpecialty.com)

 CAHILL  
SERVICES

 TCR  
Total Construction Rentals

 CHI  
COMPANIES

INDUSTRIAL  
DRYING  
SOLUTIONS  
 IDS

 MIDSTREAM  
EQUIPMENT



**REIC SPECIALTY**

[REICSPeCIALTY.COM](http://REICSPeCIALTY.COM) | [INFO@REICSPeCIALTY.COM](mailto:INFO@REICSPeCIALTY.COM)