

1.5 TON PORTABLE WATER-COOLED AC



A compact, deluxe portable spot cooler delivering 18,000 BTUH of water-cooled performance — ideal for server rooms, control rooms, and indoor spaces where air-cooled units aren't feasible.

Product Features

- Solid-state electronic controller with large LED display
- Manual or auto 6-speed fan control
- Internal condensate pump w/ overflow alert (20' vertical lift)
- Water regulating valve & high-pressure safety switch
- Swivel ball-bearing casters with locking fronts
- Washable electrostatic air filter

TECHNICAL SPECS	
Unit Model	OWC1811
Cooling Capacity	18,000 BTUH
EER	13.8
Voltage	115V / 60Hz / 1PH
Amps (Run / Inrush)	11.3 A / 69 A
Total Watts	1,300
Plug Type	5-15P, LCDI
Operating Range	65° – 105°F (Indoor only)
Compressor	Rotary, 1½ HP — LRA 63
Evap Air Flow (High)	600 CFM
Evap Motor	⅛ HP
Refrigerant	18 oz R-410A
Water In / Out / Drain	3/8 MF (each)
Condenser Water @ 60°	1.1 GPM
Condenser Water @ 85°	4.5 GPM
Dimensions (H x W x D)	45.7" x 21.5" x 16.0"
Net Weight	155 lbs

Cooling capacity rated at 80°DB / 67°WB return air with 85°EWT and 105°LWT. Dedicated circuit and time-delay fuses / circuit breakers recommended. Condenser water usage varies with water and ambient conditions.