

5 TON DELUXE PORTABLE WATER-COOLED AC



A heavy-duty deluxe portable spot cooler delivering 60,100 BTUH of water-cooled performance — ideal for server rooms, manufacturing floors, and indoor spaces where air-cooled units aren't feasible.

Product Features

- Solid-state electronic controller with large LED display
- Manual or auto 6-speed fan control
- Internal condensate pump w/ overflow alert (20' vertical lift)
- Water regulating valve & high-pressure safety switch
- Swivel ball-bearing casters with locking fronts
- Washable electrostatic air filter

TECHNICAL SPECS	
Unit Model	OWC6012
Cooling Capacity	60,100 BTUH
EER	12.0
Voltage	208–230V / 60Hz / 1PH
Amps (Run / Inrush)	23.7 A / 165 A
Total Watts	5,000
Plug Type	6-30P
Operating Range	65° – 105°F (Indoor only)
Compressor	Scroll, 5 HP — LRA 158
Evap Air Flow (High)	1,950 CFM
Evap Motor	1 HP
Refrigerant	52 oz R-410A
Water In / Out	5/8" MF
Drain	3/8" MF
Condenser Water @ 60°	3.8 GPM
Condenser Water @ 85°	15 GPM
Dimensions (H × W × D)	53.2" × 28.2" × 29.2"
Net Weight	375 lbs

Cooling capacity rated at 80°DB / 67°WB return air with 85°EWT and 105°LWT. Dedicated circuit and time-delay fuses / circuit breakers recommended. Condenser water usage varies with water and ambient conditions.