

150 KW ELECTRIC HEATER



The 150E electric heater offers 3 stages of heating @ 60 kW, 90 kW, & 150 kW. The unit is weatherproof making it outdoor rated and has the ability to recirculate by use of return ducting. With 100% clean, dry, emission-free air it eliminates the need for mechanical ventilation and provides supply air free of air contaminants & pollutants. The 150E aids in managing humidity levels and preventing condensation & mold growth. The unit is equipped with a mounted thermostat and a slim profile allowing it to fit through 36" door openings and to be situated in confined areas. This high static unit is capable of 200' max duct runs.

TECHNICAL SPECS

BTU / Hr Input	Stage 1 = 205,000 (60 kW) Stage 2 = 307,000 (90 kW) Stage 3 = 512,000 (150 kW)
Voltage	480V
Phase	3PH
Amp Draw	Stage 1 = 87 A (60 kW) Stage 2 = 138 A (90 kW) Stage 3 = 196 A (150 kW)
Connection	Camlock
Fuel	Electric
Air Delivery	14,500 CFM
Static Pressure	6.5" (200' Max Supply)
Air Outlet	24" Inlet / 20" – 24" Outlet
Weight	950 lbs
Dimensions (L x W x H)	68" x 31.5" x 56"
Forklift Pockets	Yes
Lifting Eyes	Yes
Casters	Yes
Certifications	OMNI Labs

Product Features

- 3 stages of heating @ 60 kW, 90 kW, & 150 kW
- Weatherproof — outdoor rated
- Recirculate by use of return ducting
- High static — capable of 200' max duct runs
- Fits through 36" door openings; slim profile for confined areas
- 100% clean, dry, emission-free air
- Mounted thermostat; Camlock connection

