

# 60 KW ELECTRIC HEATER



The 60E electric heater offers 3 stages of heating (20 kW, 40 kW, & 60 kW). With 100% clean, dry, emission-free air it eliminates the need for mechanical ventilation and provides supply air that is free of air contaminants & pollutants. The 60E aids in managing humidity levels and preventing condensation & mold growth. The unit is equipped with a mounted thermostat and a slim profile allowing it to be situated in confined areas.

## TECHNICAL SPECS

<b>BTU / Hr Input</b>	Stage 1 = 68,240
	Stage 2 = 136,480
	Stage 3 = 204,720
<b>Voltage</b>	208V
<b>Phase</b>	3PH
<b>Amp Draw</b>	Stage 1 = 56 A
	Stage 2 = 112 A
	Stage 3 = 168 A
<b>Connection</b>	Camlock
<b>Fuel</b>	Electric
<b>Air Delivery</b>	4,500 CFM
<b>Static Pressure</b>	3"
<b>Weight</b>	300 lbs
<b>Dimensions (L x W x H)</b>	51.5" x 22" x 35.5"
<b>Forklift Pockets</b>	No
<b>Lifting Eyes</b>	Yes
<b>Casters</b>	Yes
<b>Certifications</b>	OMNI Labs

## Product Features

- 3 stages of heating (20 kW, 40 kW, & 60 kW)
- 100% clean, dry, emission-free air
- Eliminates the need for mechanical ventilation
- Mounted thermostat
- Slim profile for confined areas
- Camlock connection
- Casters for easy movement

