

5 TON HORIZONTAL AC / DEHUMIDIFIER



The indoor & outdoor rated AHSC-60 is a horizontal 5-ton portable air conditioning system rated at 60,000 BTU for construction, industrial & commercial applications. At only 29" wide it can fit through most single-man doors and is ideal for applications where space is limited.

TECHNICAL SPECS

BTU / Hr Input	60,000 (5 Ton)
Voltage	460V
Phase	3
Cooling Amps	10.6 A (20 A Circuit)
Connections	Camlock Male
Evap Air Flow	1,620 CFM
Supply Air Outlet	(1) 12" Round (50' Max)
Return Air Inlet	(1) 16" Round (50' Max)
Cond Air Flow	3,240 CFM w/ VFD
Condenser Outlet	N/A
Weight	586 lbs
Dimensions (L x W x H)	57" x 29" x 51"
Forklift Pockets	Yes
Casters	Yes
Condensate Pump	Yes (External)
Certifications	ETL & CE
Operating Range	50°F – 118°F

Product Features

- Indoor & outdoor rated
- Horizontal chassis — only 29" wide, fits through most single-man doors
- Camlock Male connections — 460V / 3PH
- VFD condenser fan (3,240 CFM)
- External condensate pump
- Forklift pockets & casters
- Operating range 50°F – 118°F