

2 TON AC / DEHUMIDIFIER



This versatile 208/230V portable air conditioning unit is suitable for various applications, including computer rooms, hospitals, schools & universities, process cooling, industrial environments, special events, and emergency short-term cooling needs. The compact unit thermostatically controls temperature while managing humidity levels and preventing condensation & mold growth. It can be equipped with supply duct extensions, a remote thermostat, evaporator & condenser air plenums, a condensate collection tank, or a condensate pump for a wide array of applications.

TECHNICAL SPECS	
BTU / Hr Input	21,000
Voltage	208V / 230V
Phase	1
Amps	11.1 A
Circuit Breaker Size	15 A
Plug Configuration	NEMA 6-15p
Evaporator Air Flow	465 – 560 CFM
Condenser Air Flow	1,190 – 1,380 CFM
Evaporator Air Outlet	(2) 5" Round (10' Max)
Condenser Air Outlet	(1) 12" Round
Filter Type	Washable Media
Operating Conditions	64°F – 113°F
Weight	196 lbs
Dimensions (L x W x H)	26.4" x 20.6" x 41.0"
Condensate Pump	Optional
Condensate Tank	Optional
Certifications	ETL

Product Features

- Thermostatic temperature control
- Manages humidity, prevents condensation & mold growth
- Washable media filter
- NEMA 6-15p — 208/230V outlet
- Optional accessories: condensate pump, collection tank, remote thermostat, supply duct extensions, evaporator & condenser air plenums