

3 TON AC / DEHUMIDIFIER



This versatile 208/230V portable air conditioning unit is suitable for various applications, including computer rooms, hospitals, schools & universities, process cooling, industrial environments, special events, and emergency short-term cooling needs. The compact unit thermostatically controls temperature while managing humidity levels and preventing condensation & mold growth. It can be equipped with supply duct extensions, a remote thermostat, evaporator & condenser air plenums, a condensate collection tank, or a condensate pump for a wide array of applications.

TECHNICAL SPECS

BTU / Hr Input	37,000
Voltage	208V / 230V
Phase	1
Amps	19 A
Circuit Breaker Size	30 A
Plug Configuration	NEMA 6-30p
Evaporator Air Flow	776 – 882 CFM
Condenser Air Flow	1,660 CFM
Evaporator Air Outlet	(3) 5" Round (10' Max)
Condenser Air Outlet	(1) 16" Round (25' Max)
Filter Type	Washable Media
Operating Conditions	64°F – 113°F
Weight	254 lbs
Dimensions (L x W x H)	33.3" x 26.0" x 52.4"
Condensate Pump	Optional
Condensate Tank	Optional
Certifications	ETL

Product Features

- Thermostatic temperature control
- Manages humidity, prevents condensation & mold growth
- Washable media filter
- NEMA 6-30p — 208/230V outlet
- Optional accessories: condensate pump, collection tank, remote thermostat, supply duct extensions, evaporator & condenser air plenums