

# 500,000 BTU INDIRECT-FIRED HEATER



By drawing 100% fresh air, indirect-fired heaters reduce air contaminants & pollutants while managing humidity levels and preventing condensation & mold growth. The thermostatically controlled air also prevents negative pressure that can lead to drafts and outside air infiltration. The IDH500QR is equipped with a heat exchanger that keeps the heated air and the combustion separate for the ultimate clean, dry air supply. Like a permanent air handler, the IDH500QR provides evenly distributed, warm, dry air.

## TECHNICAL SPECS

<b>BTU / Hr Input</b>	500,000
<b>Voltage</b>	120V
<b>Phase</b>	1PH
<b>Running Amps</b>	17.6 A
<b>Fuel</b>	#1 or #2 Diesel (42 gals)
<b>Air Delivery</b>	4,800 CFM @ 3.5" ESP
<b>Air Outlet</b>	12" x 2 or 16" x 1
<b>Air Inlet</b>	16" x 1
<b>Weight</b>	580 lbs
<b>Dimensions (L x W x H)</b>	85" x 30" x 52"
<b>Heat Exchanger</b>	Yes
<b>Forklift Pockets</b>	No
<b>Lifting Eyes</b>	Optional
<b>Casters</b>	Yes
<b>Certifications</b>	CSA / ETL

## Product Features

- Heat exchanger keeps heated air and combustion separate
- Draws 100% fresh air for clean, dry air supply
- Provides evenly distributed, warm, dry air like a permanent air handler
- Thermostatically controlled
- Reduces air contaminants & pollutants; manages humidity
- #1 or #2 Diesel fuel (42 gal)

