

60 KW ELECTRIC HEATER



The 60E electric heater offers 3 stages of heating. With 100% clean, dry, emission-free air it eliminates the need for mechanical ventilation and provides supply air that is free of air contaminants & pollutants. The 60E aids in managing humidity levels and preventing condensation & mold growth. The unit is equipped with a mounted thermostat and a slim profile allowing it to be situated in confined areas.

TECHNICAL SPECS	
BTU / Hr Input	Stage 1 = 82,000 (24 kW) Stage 2 = 164,000 (48 kW) Stage 3 = 205,000 (60 kW)
Voltage	480V
Phase	3PH
Amp Draw	Stage 1 = 30 A (24 kW) Stage 2 = 60 A (48 kW) Stage 3 = 75 A (60 kW)
Connection	Camlock
Fuel	Electric
Air Delivery	1,765 CFM
Air Outlet	14" Outlet
Weight	125 lbs
Dimensions (L x W x H)	46" x 20" x 25"
Forklift Pockets	No
Lifting Eyes	No
Casters	Yes

Product Features

- 3 stages of heating (24 kW, 48 kW, & 60 kW)
- 100% clean, dry, emission-free air
- Eliminates the need for mechanical ventilation
- Mounted thermostat
- Slim profile for confined areas
- Camlock connection
- Casters for easy movement